


POWER TRIODE

SHORT FORM SPECIFICATION


3CX3000A1/8238

Plate Dissipation (Max.)	4000 W
Grid Dissipation (Max.)	50 W
Frequency for Max. rating (CW)	MHz
Amplification Factor	5
Filament/Cathode	Thoriated Tungsten
Voltage	7,5 V
Current	51,5 A



Capacitance	Grounded Cathode
Input	pF
Output	pF
Feed through	pF

Cooling	Forced Air
Base	Flexible
Air Socket	
Air Chimney	
Length	9,00 in; 228,6 mm
Diameter	4,16 in; 105,7 mm
Weight	6,2 lb; 2,8 kg
Operating Position	Vertical, base up or down



Class of Operation	Type of Service	Maximum Ratings			Typical Operation			Output Power (Watts)
		Plate Voltage (Volts)	Plate current (Amps)	Plate Voltage (Volts)	Screen Voltage (Volts)	Plate Current (Amps)	Drive Power (Watts)	
AB	Grid Driven AF Amplifier or Modulator	6000	2,5	5500	---	2,2	---	8250



TUNGSTEN VACUUM ELECTRONICS

Factory: H-2120 Dunakeszi
Rétipálya

Tel : (36)-27-546-570
Fax : (36)-27-546-571

E-mail: Info@tungsten.hu
Web: www.tungsten.hu